

$\frac{\text{Datasheet}}{\text{NG}1000}$

Rev-2.6.5

MAIN OFFICES | HQ THAT NEED ENTERPRISE-GRADE PERFORMANCE & SECURITY



NEXT-GEN APPLIANCE

- Gigabit Interface
- Easy & User-Friendly GUI
- Zero Touch Provisioning (ZTP*)

THREAT MANAGEMNT

- Next-Gen Firewall
- Next-Gen Security: IDP/IDS/WAF
- Gateway Level AV & Anti-Spam
- Geo IP Fencing
- Web & Application Filter
- Malware Prevention
- Zero day Protection(ZDP)
- SSL Inspection

PERSISTENT CONNECTIVITY

- Multi WAN Uplinks
- Load balancing & Link Aggregation
- Orchestrated SD-WAN Topologies (Hub & Spoke, Hub MESH, Branch MESH)
- Policy-based Routing (BGP,OSPF & Static Routes)
- Inbound Link Load Balancing (ILLB)
- High Availability (HA)
- Integrated LTE (USB and dongle LTE)
- Latency Mitigation (Intelligent path selection)

PRODUCTIVITY ASSURANCE

- AAA | HotSPOT Gateway
- QoS | Bandwidth Mgmt.
- SD-WAN
- User & Guest Mgmt.
- Surfing & Threat Reporting
- Traffic Analyser
- On-Appliance Reporting & Monitoring

SECURE ACCESS

- Secure SSL VPN (Client-Site & Site-Site)
- IPSec VPN
- Crypto VPN (Client-Site & Site-Site)





Specifically designed for Mid to Large Business Enterprise, the NG1000 NGFW provides Gb performance with all the features and tools available in High end appliances, 1U rack-mountable unit and with a budget-friendly cost. Every business face similar threats and network demands as larger enterprises, and thus should be protected with the same corporate-level of Internet security and Next-Gen Firewall features, without paying the corporate-level price.

It comes with built in AAA | User Management Hotspot functionalities for individual user control on both wired and wireless network. It also helps to provide secure Internet access to guest along lawful Tracking & Filtering with detailed in-built logs and reports on every configured features. Its SD-WAN helps Simplified connectivity, and strong security for remote branches of all sizes

Performance and security: NG1000 is versatile, scalable, robust & rack mountable. With throughput that can reach 40.0+ Gbps, look no further for better value and performance to secure next generation traffic.

FEATURES	HARDWARE SPECIFICATIONS
Ethernet Interfaces (Fixed)	8 /12 GbE
Connectivity Modules (Optional)	Yes - SFP / SFP+
Firewall Throughput	50.0 Gbps
Concurrent Sessions	2,00,00,000
New Sessions / Sec.	3,00,000
SSL VPN Throughput	5.5 Gbps
NG FW Throughput	9.5 Gbps
AV Throughput	7.0 Gbps
IPS Throughput	10.0 Gbps
Storage-SSD	256~512 GB
Memory /Max	16 /32 GB
Firewall Policies	Unrestricted
Maximum Connections	Unrestricted
Inbound NAT Connection	Unrestricted
Local User Database	Unlimited
Swappable Components	Power Supply -Internal (optional)
Rated for concurrent Users /Devices	1000+

SPECIFICATIONS

NETWORKING & SD-WAN

- Multiple WAN link with SD-WAN routing, Failover, and Fail-back

- over, and Fail-Dack
 Operating modes: NAT/route, transparent
 (bridge), and mixed mode
 Configurable LAN/WAN/DMZ Ports
 NAT & ALG Support DNAT , SNAT , PAT
 Routing Static, Dyn. , Source , Destination &
 Policy based
- Policy based
 Policy Rule: predefined, custom & Grouping
 Authentication, Authorization & Accounting.
 Support Multicast Forwarding, VLAN Tagging
 Static, DHCP, PAP/CHAP Support

NETWORK SECURITY

- Stateful & Deep Packet Inspection Firewall
 Application Visibility & Control.
 Demilitarized Zone (DMZ)

- Zone based access control list.

- Zone based access control list.
 Access scheduling
 Flooding detection and protection
 Stops all types of DoS; Prevents DNS Spoofing & Flooding, Bypass Websites, Packet Capturing
 IP-Mac bind, MAC Whitelist / Blacklist.
 Comprehensive DNS policy

- LINK LOAD BALANCING Bi-directional link load balancing
- Outbound link load balancing includes policy based routing and weighted, and dynamic detection
- Inbound link load balancing supports Smart DNS
- & dynamic detection
 Automatic link switching based on Traffic, latency, jitter, connectivity etc.
- Link health inspection with ARP, PING, and DNS

URL FILTERING

- Web or URL / IP / Geography / Keyword / Port / Application Filter
- Block predefined categories on specific time
 Create | Edit | Delete Manual Categories & Add exception

- exception
 Manually defined web filtering based on URL, web content. Key word and MIME header
 Web filtering profile override: allows admin to temporarily assign different profiles to User/IP
 Web filter local categories and category rating override
- Additional web filtering features:
- Force Safe search
- Exempt scanning encrypted connections on certain categories for privacy

USER | GUEST MANAGEMENT | AAA

- ■ID & Password login fixed users
- Authentication- LDAP | Radius | Local User DB
- Approval-based ,Social Media & OTP based login
- ■BYOD Self & Voucher Registration with OTP
- ■Create users with auto-expiry, Renew & Block
- Seamless connectivity from Wired to W-LAN ■ Auto Login / No Authentication after First Login
- Auto login based on IP & MAC or combination
- ■Concurrent logins, auto MAC binding
- Easy migration import/export data
- ■Restrictions based on Device & OS
- ■Create user groups & apply policies
- Allow login only when user comes from specific segments

BANDWIDTH MANAGEMENT | OoS

- Define enhanced quality of service (QoS)
- Max/Guaranteed bandwidth tunnels or IP/User basis
- Bandwidth allocated by time, priority, or equal bandwidth sharing
- Restrict users based on data, b/w &time
 Individual and shared bandwidth quota
- Contention ratio based bandwidth allocation.
- Schedule based committed & burstable b/w. Configure multiple b/w policy on a user at different hours of day

VIRTUAL PRIVATE NETWORK

- WIRTUAL PRIVATE NETWORK
 Modes: Site-to-Site, Remote Access VPN
 SSL VPN TCP/UDP tunnelling with failover
 Encryption 3DES,DES,AES, Blowfish
 Hash algorithms MD5, SHA-1, SHA-2
 Authentication pre-shared key, certificates
 Supports IKEv1 and IKEv2.
 DH groups 1, 2, 5, 14, 15, 16, 17...
 NAT traversal & PFS support
 SSL authentication AD, LDAP, radius, local
 Multi-layer client authentication certificate, username/password.mac address. OTP*
- username/password ,mac address , OTP*
 Network access Split and Full tunnelling
 Granular access control to all network resources
 Administrative controls session timeout, DPD

- User and group policy enforcement

- Multicast support over SSL VPN
 View and manage IPSEC and SSL VPN connections
 Supports SSL VPN clients that run Windows, Linux,
 iOS & Android

ROUTING

- Static Routing
- Dynamic Routing
- RIP v1 / v2
- OSPE

INTRUSION PREVENTION

- Protocol anomaly detection, rate-based detection, custom signatures, manual, automatic push or pull signature updates, integrated threat encyclopaedia.
- IPS Actions: default, monitor, block, reset (attackers IP or victim IP, incoming interface) with expiry time.
- IDS sniffer mode
 Predefined prevention configuration.

ANTI-VIRUS & ADVANCE THREAT

- Virus, Worms, Trojan detection & removal Spyware, Malware, Phishing, Bot & Pharming protection, Zero Day Protection (ZDP).
- Manual, automatic push or pull signature updates.
 Scans HTTP/S, FTP, SMTP/S, POP3, IMAP.
 Block files based on their type.
 Threat logs with action.

- Compressed file virus scanning.
- Spam filtering

ATTACK DEFENCE | WAF

- Abnormal protocol attack defence.
- Anti DoS / DDoS, including SYN Flood, UDP Flood, DNS Query Flood defence, TCP fragment, ICMP fragment etc.
- ARP attack defence

DATA LEAKAGE PREVENTION

- Restricts file upload over HTTP, FTP, P2P and other file sharing applications.
 Blocks file transfer (upload & Download) over IM like Facebook, Whats-app & other Social Sites
 Controls file upload /download over HTTPS/SSL
- websites
- Logging & Reporting in accordance to HIPAA, CIPA

SYSTEM MANAGEMENT

- System Configuration Backup / Restore Auto/ Manual backup of User & Threat Logs
- Enable appliance & PMS remote access Set auto/manual firmware updates

- Create Child Admins and check logs Set NTP , SMTP Email Integrate Syslog, SNMP, Net-flow
- Three levels of users: Admin | Operator | Monitor Dynamic real-time dashboard status and drill-in monitoring widgets



LOGS | REPORTING | MONITERING

- Real-time traffic statistic and analytics
 User Management & Account Expiry Report
 Bandwidth ,Data usages & Session Report

- Web Browsing & Records surfing logs of each user Search logs based on User, IP, Site, Time & File Type Change Log Report / Activity Timeline
 Comprehensive event logs: system & admin activity routing & networking, VPN, user authentications,
 User & System based overall and user wise analytics
- Real Time monitoring Tools to get visibility into network Traffic & Bandwidth consumption
- On-Appliance (Local) Logging and reporting facilities Reports can be exported in PDF, Word and via Email System information such as concurrent session, CPU, Memory and temperature
- Support traffic information collection and forwarding via Net-flow

CAPTIVE PORTAL CAPABILITIES

- Intuitive self-service portals for users.

- Customise captive form input fields.
 Mobile/desktop responsive login page.
 Social media based login, mac based auto login.
 Create hourly and day based plans with FUP.
 Accounting based on hours, days, data transfer.

SMS GATEWAY

- Pre-configured SMS gateway*
- Click –n-configure custom gateway
 Facilitates different message templates

- Centrally manage ,Single Pane visibility .Network Monitoring &Failure Recognition
- Topology view, Data & App Activity, Ver. Upgrade.

ALERT MANAGEMENT

- Real-time alerts to user on data consumption limit, voucher expiry etc.
- Real-time alerts to admin on link failure & Speed, Remote Access etc.
- Schedule Alerts for specific reports.

VIJI NERABII ITY ASSESSMENT

- Scans LAN Devices for vulnerability
- Generates summary and detailed reports of found possible threats

CUSTOM DEVELOPMENT

- Personalized development on request*
- Third party application Integration*

- **HIGH AVAILABILITY** Active-Passive with state synchronizations
- Stateful Failover to Keep-Alive Sessions Redundant heartbeat interfaces

- **HARDWARE**
- From factor- 1U
- Memory / Max -16 / 32 GB
 SSD 256~ 512 GB
- Modularity Copper and Fibre Interfaces. 2 USB Ports, 1 VGA, 1HDMI
- Dimension-(mm)-(HxWxD)- 44x430x360
- Weight- 5.5 Kg

- **POWER AND RELIABILITY**
- Power 90 ~ 264V@47–63Hz, 220W ATX ■ Redundant PSU Optional

Storage Temperature

- Internal Hot Swappable-optional
- Typical Power Consumption- 80 ~100W
 Operating Temperature (0°C ~ 40°C)
 Storage Temperature (-20°C ~+70°C)

Relative humidity - 10% - 90%, no condensing

All specification and photos are subject to change without prior notice

1. Maximum throughput performance is measured under ideal test conditions using industry standard performance test tools.

2. Firewall UDP throughput performance is based on RFC 2544 guidelines. 3. All Performance values are up-to or rough guideline only and vary depending on system configuration. 3. IPS throughput (http) measured using default IPS rule set and 512KB object size. 4. VPN throughput measured using multiple tunnels with 512KB response size. 5. Testing done with multiple flows through multiple port pairs. +if all slot populated

www.netxgate.com | sales@netxgate.com | +91-817881-3626